

Kodak

Production Matte Paper / 170g

KODAK Production Matte Paper / 170g provides users the ability to print high-quality, low-cost photos on a smooth, bright white surface. Production Matte Paper covers the application spectrum, and is perfect for architectural drawings or full-color photos. It provides high ink-load retention needed for saturated colors, quality images, and brilliant colors. This paper can be thermally laminated, making it ideal for producing high-impact graphics. It is often used by shops who want a low-cost way to produce high volumes of POP displays, posters, or color accurate renderings. It is universally compatible with thermal and piezo pigmented and dye inks, and is instant-dry.

Properties	Specifications
Material	Matte photo paper
Gauge	7 mil, 170g
CIE Whiteness	150
Opacity	>63
Printer/Ink Compatibility	Dye/Pigment
Software Settings	The bond or uncoated paper setting in most RIPs is a recommended starting point. However, a custom ICC profile is ideal for optimal results.
Light-fastness	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
Finishing/Post Processing	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.

Product Performance & Suitability: All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.

